

DS-KAW50-1

- 12 VDC, 50 W output power supply for door station with box
- Short circuit protection, over load protection, and over power voltage protection
- 105 °C long life electrolytic capacitor
- 5 seconds 300 VAC surge voltage input tolerance
- High working temperature up to 70 °C

▪ Specification

Device interfaces	
Power supply input	1, 100 VAC to 240 VAC
Power supply output	Max. 12 VDC, 4.17 A
General	
Weight	Net weight: 1.835 kg Gross weight: 2.504 kg
Working temperature	Operation: -10 °C to 70 °C (14 °F to 158 °F) Storage: -25 °C to 85 °C (-13 °F to 185 °F)
Working humidity	< 95% (no-condensing)
Cooling system	Convection
Dimension (L x W x D)	246 mm × 266.4 mm × 79.6 mm (9.69" × 10.49" × 3.13")
Power supply	100 VAC to 240 VAC
Power consumption	50 W

▪ Available Model

DS-KAW50-1

▪ Accessory



DS-KV8113-
WME1(C)/Flush



DS-KV8213-
WME1(C)/Flush



DS-KD8003-
IME1(B)/Surface



DS-KH6320-
WTE1



DS-KH9510-
WTE1(B)



DS-KD8003-
IME1(B)/NS



DS-KH7320-WTE1-
W#poland



DS-KD9633-WBE6



DS-KH6320-WTDE1



DS-KD9203-TE6



DS-KH6350-TE1



DS-KV8213-
WME1(C)



DS-KH8350-WTE1



DS-KH6320-LE1(B)



DS-KH7320-
WTE1#poland



DS-KV6103-
PE1(C)



DS-KD9203-FTE6



DS-KD3003-E6



DS-KD9203-FE6



DS-KD9203-E6



DS-KD9633-E6



DS-KH6350-WTE1



DS-KH6320-TE1



DS-KD8023-E6



DS-KH6320-TDE1



DS-KV8113-
WME1(C)



DS-KH8350-TE1



DS-KV8413-
WME1(C)/Flush



DS-KV6113-
PE1(C)



DS-KH9310-
WTE1(B)



DS-KD8103-E6



DS-KH6351-WTE1



DS-KV8413-
WME1(C)



DS-KV6113-WPE1(C)



DS-KH6351-TE1



DS-KB8113-IME1



DS-KH6320-
LE1(B)/White



DS-KD8003-
IME1(B)/S



DS-KD9403-E6



DS-KD8003-IME1(B)



DS-KH8520-WTE1

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq